How to tell the difference between Acorn_rev2 and Acorn_rev3
Acorn_rev2 has FIXED green screw terminal blocks
Acorn_rev3 has REMOVABLE green screw terminal blocks

Title: ACORN_rev3 CONNECTIONS TO TECO 7300CV	
PLC Program: acorn-mill-universal.src	
Date: 170824	Drawn by: CEM
Filename:	Sheet 1 of 1

ACORN

REV 171025

PN:

+24VDC
DRIVE OK

H1: DRIVE OK, +24VDC, IN5, IN6, IN7, IN8, 24 IN
H2: ST1, DR1, EN1, COM, ST2, DR2, EN2, COM
H3: ST3, DR3, EN3, COM, ST4, DR4, EN4, COM

H4: 24 IN, IN4, IN3, IN2, IN1

H5: COM, OC8, OC7, COM, OC6, OC5, COM, OC4, OC3, NC2, NO2, RL2, NC1, NO1, RL1
- COM
- RESET
- SPIN REVERSE
- SPIN FORWARD

RL1 TURNS ON (CLOSES) WITH RELEASE OF THE E-STOP BUTTON

H6 (DB25 connector)

H6:
- COM
- Input 4 (13)
- Input 3 (12)
- Input 2 (11)
- Input 1 (10)
- Direction 4 (9)
- Step 4 (8)
- Direction 3 (7)
- Step 3 (6)
- Direction 2 (5)
- Step 2 (4)
- Direction 1 (3)
- Step 1 (2)
- Output 1 (1)
- Output 4 (17)
- Output 3 (16)
- Input 5 (15)
- Output 2 (14)
- Chassis GND

P10 (DB9 connector)

P10:
- PIN 9 = +5VDC
- PIN 8 = B
- PIN 7 = A
- PIN 6 = Z
- PIN 5 = B\
- PIN 4 = A\
- PIN 3 = Z\
- PIN 2 = COM
- PIN 1 = N/C

FROM SPINDLE ENCODER

H8: AN GND, AN OUT
- 0-10VDC
- 0-10VDC COM
- SHIELDED ETHERNET CABLE FROM PC

ETHERNET

H9: CHASSIS, COM, COM, +24VDC, +24VDC
- 0-10VDC
- 0-10VDC COM
- 24VDC COM
- DRIVE OK

DRIVE OK
+24VDC

DRIVE OK
+24VDC

TECO 7300CV

- 24G (0V COMMON)
- S6
- S2 — *SET SW1 TO NPN
- S1 — *SET SW2/SW3 TO 0~10VDC
- AIN
- AGND
- R1C
- R1A
- GROUND

POWER IN:
- L1/R
- L2/S
- L3/T
- GROUND

BRAKING RESISTOR
BRAKING RESISTOR

3 PHASE POWER OUT:
- T1/U
- T2/V
- T3/W
- GROUND

SEE TECO MANUAL FOR POWER AND MOTOR CONNECTIONS AND PARAMETER SETTINGS.

MEANWELL S-25-24:
- BLK — -V (24V COM)
- YEL — +V (+24 VDC)
- GRN — GRN OR GRN/YEL — OUTPUT +24 VDC 1.1 AMP
- L — BLK OR BRN
- N — WHT OR BLU

110VAC

OPTIONAL CONNECTIONS ARE BLUE
GROUNDS ARE GREEN
110VAC IS VIOLET