



NEW WINDOWS ARE TO BE DUAL GLAZED

DOOR SCHEDULE				
E	DESCRIPTION	REMARKS		
"x1-3/8"	HOLLOW CORE	₩₩₩₩\$₩₩₽₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩₩		
3"x1-3/8"	POCKET DOOR			
B"x1−3/8"	SLIDING DOOR	TEMP.GLASS		
DOOR		,		

## WINDOW SCHEDULE

E	DESCRIPTION	REMARKS
3'-0"	SINGLE HUNG	TEMP.GLASS
WINDOW		

INDICATES 26W COMPACT FLUORESCENT TRIPLE 4 PIN

BRACK LIGHT (+ 5'-6" ABOVE FLOOR

OR ENTRY) (6'-8" ABOVE FLOOR AT SIDE OR REAR) TO BE EITHER HI.EFF.FLUOR. OR INCANDESCENT W/ OCC.SENSOR AND PHOTOCELL

HI EFFICACY LUMINAIRES MUST BE PIN BASED.

**DUPLEX OUTLET @40" ABOVE FLOOR** 

PROVIDE MECHANICAL VENTILATION CONNECTED DIRECTLY TO THE OUTSIDE CAPABLE OF PROVIDING FIVE AIR CHANGES PER HOUR IN BATHROOMS, WATER CLOSET COMPARTMENTS, LAUNDRY ROOMS AND SIMILAR ROOMS.

PHOTOELECTRIC HARD WIRED SMOKE ALANRMS WITH A BATTERY BACKUP ARE REQUIRED. ALARMS SHALL SOUND AN ALARM AUDIBLE IN ALL SLEEPING AREAS OF THE DWELLING UNIT WICH THEY SERV. ALL SMOKE ALARMS SHALL BE APPROVIDING & SAFETY

3. GROUND-FAULT CIRCUIT-INTERRUPPTERS (GFI) PROTECTION FOR ALL 125V, SINGLE PHASE, 15 & 20 AMP BATHROOM AND

6. PROVIDE ULTRA FLUSH WATER CLOSET FOR ALL NEW CONSTRUCTION MAX 1.6 GAL. EXISTING SHOWERHEADS AND TOILETS MUST BE

7. PROVIDE 70" HIGH NON-ABSORBENT WALL ADJACENT TO SHOWER AND APPROVED SHATTER-RESISITANT MATERIALS FOR

ALL SHOWERS AND TUB-SHOWERS SHALL HAVE EITHER A PRESSURE BALANCE OR A THERMOSTATIC MIXING VALVE.

REGISTERED	NO. C53080 Exp: 06/30/0	A SERVICE
A.	EOFCALIFO	RHIT

ITY OF DOWNE

78

This set of pinns and accordenatory weight here ob at all times and it is unusulated to rease any state

be held to peoné or th'or an epercent :

REAGER OF SOULT

REVISIONS			BY:
D. DESIGN, INC.	19562 VENTURA BLVD. #217	TARZANA, CA 91356	PHONE 818-344-4449
CDIFFIN FAMILY TDUICT		/805 PUKITAN SI.	DUWNEY, CA 90242

12/06/07

07-290

A2

<sup>4LE:</sup> 1/4"=1'-0"

AWN: MF